SAGEM PHONEFAX 47TS

- Inkfilm Fax
- Telephone
- Answering Machine
- Copier
- SMS Function*
- Sudoku

SAGEM

SAGEM PHONEFAX 47TS

Technical Specifications

INK-FILM FAX
- ITU Group 3 compatible (T.30 standard/T.30 new)
- 14.400 bps modem speed, auto fall back
- Horizontal resolution: 8 pixels/mm
  vertical resolution standard: 3.85 lines/mm
  vertical resolution fine: 7.7 lines/mm
- Page header, automatic redial
- Sending report with reduced copy of the first page
- Printing method: thermal transfer
- 10 page automatic document feeder (ADF)
- Predefined fax forms
- Timer function (send later)
- Up to 50 page memory
- Group broadcasting
- Easy polling (receive and send)
- Paper tray up to 50 sheets
- Cordless phone management
- Sudoku printing with solutions
  (easy - medium - tough - devil)

TELEPHONE
- 200 name dial entries
- 10 ringer melodies
- Caller identification (CLIP)*
- Distinctive ring tones**
- 10 short dial keys
- On hook dialling
- Handsfree speaking
- Chain dialling
- Redial of the last 10 numbers
- Outgoing call log print

ANSWERING MACHINE
- Recording time up to 30 minutes
- Direct message access (first 9 messages)
- Current call recording
- Pre-recorded outgoing messages
- Message forwarding
- VIP-Code

COPIER
- Multicopy up to 15 pages
- Fine-/photo-resolution
- Zoom-function (enlarge/reduce)
- 64 grey scales

SMS-FUNCTION* OVER THE LANDLINE
- Alphabetical keyboard (QWERTY)
- Send and receive SMS over the landline
- Print and save SMS-messages (up to 30)
- Broadcasting (up to 5 recipients)
- Draft printing of SMS before sending
- SMS-forwarding
- SMS notification

* Depends on the availability of the service on the local operators network
** Depends on availability of caller identification

Logistical Data

9 NC:	**28809XXXX**
TYPE NUMBER:	**SPFX47TS/XXX**
EAN CODE:	**342516018XXXX**
DESIGNED FOR:	**PSTN/PABX**
POWER SUPPLY:	**195 - 264V AC/ 47 - 63HZ**

POWER CONSUMPTION

· Stand by:	< 1,5 W
· Transmission:	typ. 15 W
· Reception:	typ. 15 W
· Copy:	typ. 15 W
· Telephone conversation:	typ. 4 W

DISPLAY
- Liquid crystal-display (LCD), 16 characters/ 1 line, European characters

INSTALLATION
- Easy-install menu and help pages

DIMENSION (WXDXH)

· Unpacked:	313 x 195 x 126 mm
· Packed:	380 x 250 x 200 mm

WEIGHT

· Unpacked (without accessories):	2,5 kg
· Packed (incl. country kit):	3,4 kg

TEMPERATURE RANGE

· Operation:	5° C - 40° C
· Storage packed:	-25° C - 50° C
· Storage unpacked:	0° C - 45° C

RELATIVE HUMIDITY

· Operation:	15 - 85 %
· Storage packed:	5 - 95 %
· Storage unpacked:	15 - 85 %

STANDARD PACKAGE INCLUDES
- Fax machine incl. cables (main and telephone network)
- Paper tray
- Starter ink film
- User-manual including installation-guide

ACCESSORIES
- Sagem TTR400 with PLUG'N'PRINT Card/ up to 140 pages A4

© 2006 SAGEM Communication Austria GmbH.

All rights reserved.The information and specifications included are subject to change without prior notice. Sagem Communication tries to ensure that all information in this document is correct, but does not accept liability for error or omission. SAGEM is a registered brand of SAFRAN Group

www.sagem.com

SAGEM